


» **Features**

- DPDT.SPST Tactile feeling. Illuminated 12X17 & 12x12mm.
- Several LED colors options.



» **Applications**

- Operating switches in all types of electronic equipment such as audio apparatus, office equipment, communications apparatus, TV sets, VCRs, etc.

» **Specifications**

Rating	5A 125 / 250VAC or 5A 30VDC
Insulation Resistance	200MΩ Min (at 500 VDC)
Dielectric Strength	AC 500V (50/60 Hz for 1 minute)
Contact Resistance	50mΩ Max. (Initial)
Electrically Life	10,000 Cycles Min
Ambient Temperature	-25°C~ 50°C
Operating Force	190 ± 50gf single pole
	250 ± 50gf Double pole

» **LED Specifications**

Color	VR	IF	Recommended Operating Current	VF	
				Nor	Max
Red	DC 5V	20mA	20mA	1.5V	2.6V
Green	DC 5V	20mA	20mA	1.9V	2.6V
Yellow	DC 5V	20mA	20mA	1.9V	2.6V
Blue	DC 5V	20mA	20mA	3.5V	4.0V
White	DC 5V	20mA	20mA	3.5V	4.0V

For the specification about the other LEDs, please contact with sales department

» **Product selection**

SPC



FUNCTION	
A	Non-illuminated Alternate
B	Non - illuminated Momentary
AL	illuminated Alternate
BL	illuminated Momentary



APPARENT SHAPED	
S	SPDT
R	DPDT




CAP COLOR	
1	Red
2	Yellow
3	Green
5	White
T	Transparent
7	Blue



LED COLOR		
1		Red
2		Yellow
3		Green
4		Blue
6		Pure Green
7		RGB
12		Red/Yellow
13		Red/Green
23		Yellow/Green
-		Non-illuminated

» LED Circuit





» Operating characteristics

Unit: mm

Dimensions

P.C.B Layout

SPC □ LS57



SPC □ LR77

