# WS SERIES MARK SWITCH

#### **Features**

- The WS series Mark Sensors used the advanced E/O as well
  as double Side SMT technology,thus enable this series features
- $\bullet$  Small sport size  $\smallsetminus$  Dual light source  $\searrow$  Economic price.
- By using the GREEN as well as RED LED as light source simultaneously, the color discrimination capability is greatly enhanced.
- For economic purpose, the single color model is also introduced.



#### **Specifications**


Item	Standard			
Operating Voltage	12-30 VDC			
Sensing Distance	8mm or 12mm,Selectable			
Current Consumption	Less than 45mA			
Power on Reset Time	20ms			
Response Time	1ms 0.3ms for (H)			
Circuit Protection	Output short circuit. Reverse polarity of supply voltage.			
Max. Load Current	120mA			
Sealing	Conforming to IP66 (IEC).			
Cable Length	2 meter,oil retardant,gray color.			
Wiring Diagram	Brown,black,white and blue as standard. Both Light-on and Dark-on Output included.			

### **Product Selection**


Light	Source	Focus Length	Universal Output	PNP Output
Dual Color	Red,Green	12mm	WS-C2 (H)	WS-C4
	Red,Green	8mm	WS-C2A (H)	
Single Color	Green	12mm	WS-C2G	
	White	12mm	WS-C2W	WS-C4W
Dual Color	Blue,Yellow	12mm	WS-CB2 (H)	WS-CB4

### **Output Circuit**

**Universal Output** 



## **DIMENSIONS(in mm)**



#### **PNP Output**

